



uniwu®

ISO 9001

Thermodynamic St.St. 316 Steam Trap

Model: UN-317

Working Pressure: 4.5-600 PSI / PN 0.3-40

Working Temperature: 250°C / 482°F



TOS11

**UNIWU GROUP
T-ONE-S (MFG) TRADING INC.**

Sep. 2008

**THERMODYNAMIC ST.ST.316
STEAM TRAP PN40 ANSI 600 PSI.**
BODY: INVESTMENT CF8M
SCREWED END TO BS21, ANSI B2.1
SIZE: 1/2"~1"

MODEL: UN-317



**THERMODYNAMIC ST.ST.316
STEAM TRAP PN40 ANSI 600 PSI.**
BODY: INVESTMENT CF8M
SCREWED END TO BS21, ANSI B2.1
SIZE: 1/2"~1"

MODEL: ST-02



**THERMODYNAMIC ST.ST.316
STEAM TRAP PN40 ANSI 600 PSI.**
BODY: INVESTMENT CF8M
SCREWED END TO BS21, ANSI B2.1
SIZE: 1/2"~1"

MODEL: ST-03




CAST IRON STEAM TRAP CLASS 16K
SCREWED END TO BS21, ANSI B2.1 OR
DIN-259. BODY: FC20
SIZE: 1/2"~1"

MODEL: ST-8LS




CAST IRON STEAM TRAP CLASS 16K
SCREWED END TO BS21, ANSI B2.1 OR
DIN-259. BODY: FC20
SIZE: 1/2"~2"

MODEL: ST-T3A




CAST IRON STEAM TRAP CLASS 16K
SCREWED END TO BS21, ANSI B2.1 OR
DIN-259. BODY: FC20
WITH BLOW-OFF.
SIZE: 1/2"~2"

MODEL: ST-T3B



CAST IRON STEAM TRAP CLASS 16K
FLANGED END TO JIS 10K, ANSI 150,
DIN-PN16 OR PN10. DRILLED.
BODY: FC20
SIZE: 1/2"~2"

MODEL: ST-T3F



CAST IRON STEAM TRAP CLASS 16K
SCREWED END TO BS21, ANSI B2.1 OR
DIN-259. BODY: FC20
SIZE: 1/2"~2"

MODEL: ST-T6A (MANUAL TYPE)



CAST IRON STEAM TRAP CLASS 16K
FLANGED END TO JIS 10K, ANSI 150,
DIN-PN16 OR PN10. DRILLED.
BODY: FC20
SIZE: 1/2"~2"

MODEL: ST-T6F (MANUAL TYPE)

